

ACCESSORIES DOLLIES AND SPREADER

Manfrotto dollies and spreaders maintain a tripod at a secure spread. Dollies provide instant manoeuvrability around the studio or on location and all have fast action foot controlled braking systems.



BASIC DOLLY 127



2.4kg 110cm

Designed for light and medium weight tripods. The 76mm wheels have a sure-lock feature that raises the wheels free of the ground so that the dolly rests on separate feet.

Designed for Manfrotto's Tripods: 055D, 055CL, 055PRO, 055MF3, 055MF4, 190D, 190CL, 190PRO, 190MF3, 190MF4, 458B.



PORTABLE DOLLY 127VS



3.4kg 78 to 114cm

Everything that the 127 has with the addition of variable spread to the legs. Suitable for standard and spiked feet.

Designed for Manfrotto's Tripods: 055D, 055CL, 055PRO, 055MF3, 055MF4, 190D, 190CL, 190PRO, 190MF3, 190MF4, 458B.



VIDEO DOLLY 114



8kg 112cm

Heavy duty, super sturdy dollies are designed for use with large still and video tripods. They feature large 127mm individually braked wheels with cable guards. Folds for transporting.

Designed for Manfrotto's Tripods: 058, 161MK2, 475.



FOLDING AUTODOLLY 181B



4.5kg 127cm

Single lever braking system controls all three 80mm wheels. Includes 3/8" attachment which allows you to fix a head for low angle shooting. It folds legs for transporting and storage.

Designed for Manfrotto's Tripods: 028, 058, 161MK2, 458B, 475.



TRIPOD SPREADER 165



0.65kg 80 to 130cm

Universal tripod spreader with variable diameter width controls from 80cm to 130cm.

Designed to work with most Manfrotto tripods.



TABLE CENTER POST 131TC

Geared column with clamp for table thickness from 18-38mm, for supporting a camera adjustable between 5cm and 66cm. Head not included.



AIR CUSHIONED TABLE CENTER POST 385

In view of the increasing demand for shop display systems for still & video cameras, we have produced a centre column equipped with a standard 58 mm disc and three grub screws as used on our 190 and 055 tripods. This also means the column can be combined with any head from our range. The bottom of the column has an 80mm disc which can be screwed directly to countertop/table or, alternatively, bolted to the included second disc on the underside of the countertop. Specifications: Column diameter: 30mm / 26mm Minimum Height 36cm Maximum Height 62cm Weight 1.1 kg Load capacity 10 kg. Available only in black finish.



LEVELL. CENTER COLUMN ANGLE BRACKET 553

Working with the center column in the horizontal position on Manfrotto tripod models 055, 190 and NEOTEC tripod family has always caused a slight difficulty, in that the head remains at 90° to the ground making it more difficult to position the camera correctly for shooting. Now this simple but had the most stable platform possible for filming, and that we could use ever-lighter materials, from aluminum to carbon fiber, to keep equipment weight to the bare minimum.



ACCESSORY ARM 131D B

Mounts on any column with 3/8" thread, this side arm allows positioning of two heads on a 90° perpendicular angle. Length: 600mm



SHORT COLUMN 055CCSB SHORT COLUMN 190CCSB

To improve the positioning flexibility of our tripods, a shorter center column is now available as an accessory which can be ordered separately. If you need to work with legs set at the third angle of inclination (about 60°) but still require the possibility to move the camera up and down to achieve perfect adjustment for the shot, this shorter column replaces the one supplied with the tripod.

The lengths are:
- 17.5 cm for the 055CCSB.
- 16.5 cm for the 190CCSB.
190CCSB for tripods series 190.
055CCSB for tripods series 055.



ACCESSORY ARM FOR 4 HEADS 131DD B

Similar to the 131D with the addition of two positional head mounts on the side arm allowing the possible mounting of four heads. Length: 600mm



LEV. CENTRE COLUMN 555B LEV. CENTRE COLUMN 556B

Our innovative system means you can quickly level your photo or video head without needing to make time-consuming adjustments to the length and angle of each single tripod leg. One of the most common problems in still photography and, above all, video has been resolved by Manfrotto, thanks to the use of a 50mm diameter levelling half ball mounted at the top of a tripod centre column so as to make the angle of the top plate independent of the rest of the tripod. Locking and unlocking of the half ball is via a turning grip on the bottom of the centre column, which can be removed during fitting of the column to your existing tripod. The half ball-mounted plate has a male 3/8" screw for attachment to a photo or video head, and a bubble spirit level for added ease of use.

555B for tripods series 055.
556B for tripod series 190.
PAT. PENDING



TWO SECTION CENTER COLUMN FOR 190 RANGE 190TS B

TWO SECTION CENTER COLUMN FOR 055 RANGE 055TS B

This new centre column design allows to leave the head mounted on the centre column when switching between low angle and normal shooting position. The top section can be detached without any tools, by hand-unscrewing the knob at the bottom of the column. Available in silver and lack anodised finishing. 190TS: compatible with all 190 range of tripods, supplied as a standard with the 190PRO, 190MF3, 190MF4. 055TS: compatible with all 055 range of tripods, supplied as a standard with the 055PRO, 055MF3, 055MF4 and 458B. PAT. PENDING



LOW ANGLE ADAPTER FOR 190 RANGE 190LAA LOW ANGLE ADAPTER FOR 055 RANGE 055LAA

Low angle adapter to store at the bottom of the centre column when the tripod legs angle is set to 43°, 73° and 90°. 190LAA: compatible with the tripods code 190D, 190DB, 190CL, 190CLB and 190NAT3. 055LAA: compatible with the tripods code 055D, 055DB, 055CL, 055CLB and 055NAT3.

Accessories



CAMERA BRACKET 233B



1kg

Camera flash bracket with telescopic column from 30 cm to 45 cm.



LONG LENS CAMERA SUPPORT 359



0.69kg

A very useful addition to any photographers complement of attachments. Complete with Super Clamp 035 and Mini Ball Head 482. Fully adjustable between 40cm and 60cm with a simple telescopic locking device.



ELBOW BRACKET 340



0.32kg

The "Elbow Bracket" enables one to rapidly change from a horizontal to a vertical shooting position, without having to reposition the tripod and to keep an axis of vision which is vertical to the tripod itself, thus avoiding the threat of tilting. Compatible with the following heads: 029, 229 and 488RC0. Comes complete with 1/4" to 3/8" screws.



JUNIOR ELBOW BRACKET 341



0.32kg

The Junior Elbow Bracket enables you to rapidly change from a horizontal to a vertical shooting axis, without having to reposition the tripod. Its adjustable stop prevents accidental camera rotation. Great for small & medium sized cameras equipped with telephoto lenses. Its new design allows you to use this handy accessory on all heads equipped with the 200PL type of camera plate.



FOLDING BASE FOR PROJECTOR 246

Folding down to a portable 30cm, this Danish designed base holds most projectors easily on a tripod. Tapped on the bottom for 3/8" screws.



MONITOR/PROJECTOR HOLDER 183



1kg



20kg

Made of sturdy aluminium, this 25 x 35cm platform can support up to 20kg. It is ideal as a projector or monitor stand.



TABLE SUPPORT 355

This simple table mounting support is supplied with three holes for fixing or clamping. Comes complete with the Monopod Tilt Head 234.



WALL SUPPORT 356

As for the 355 but designed to be mounted to a wall. Comes complete with the Monopod Tilt Head 234.



TELEPHOTO LENS SUPPORT 293

Support for medium telephoto lens. The length of the bracket is adjustable to take different length lenses and different diameters by tilting the Tilt Head 234RC (included). Length from head to lens support adjustable from 200 to 295mm. Attachments: 4 x 3/8" female and 3 x 1/4" female.



MACRO BRACKET FLASH SUPPORT 330B



0.35kg



1kg

Allows two flash heads to be mounted with a camera onto a tripod head. Attachments: 3/8" & 1/4" female threads & 1/4" camera fixing screw.



MICRO POSITIONING PLATE 454



0.45kg



8kg

Ideal for macro photography to make precise positioning movements to achieve the perfect framed shot, for QTVR and other precise copy/repro work, the new sliding plate has finger-tip control for hairsbreadth positioning but with a simple lock-release lever for fast set-up. Two plates can be interlocked at 90 degrees for full lateral/ forward/ /back movement (over 120mm). In extruded aluminium, the plate has 1/4" and 3/8" holes and screws for tripod and camera mounting. Dimension: 180x57,5x6mm



TOOL KIT WMANTOOL

Set of tools (2) to adjust the locking collars of most of Manfrotto's tripods, stands and Monopods. The kit comprises a PHILLIPS screwdriver TYPE 2 and a hexagonal tubular SOCKET N. 8.



ACCESSORY LONG PLATE 430

Allows two camera mounting positions. Supplied with 2 x 1/4" and 2 x 3/8" camera fixing screws. Dimension: 280x80x10mm



LEG WARMERS 380

Set of 3 Manfrotto Patented Leg Warmers, which have a zip system so they can be easily fitted and will not slip down in use. Offer good grip. Protect the legs and insulate your hands when using the tripod in cold weather. For tripods series 055. Length 355mm.

LEG WARMERS 381

For tripods series 190. Length 250mm.



ANTI THEFT PLATE 030AT



0.45kg

For heads with hexagonal plates. Key lock system for camera release and 200cm steel cable.

Accessories



CAMERA MOUNTING STUD 037

Reversible stud with 3/8" and 1/4" designed for mounting cameras flush on 035 Super Clamp.



METZ FLASH SCREW 248

A special long 1/4" camera screw used in conjunction with the hexagonal 030 camera plate which allows you to fit the Metz flash bracket.



ADAPTOR FROM 3/8" TO 1/4" 120

Converts tripod head screw from 3/8" to 1/4". Diameter: 60mm



JOINT FOR ARMS 120DF

Adapter 3/8" F-1/4" F allows using accessory arms 131D and 131DD as column extensions. Diameter: 60mm



FLASH SHOE 143S

Flash shoe.



NIKON FLASH ADAPTOR 262

Converts Nikon flash mount to universal flash bracket.



CAMERA MOUNTING ADAPTOR 208

Allows use of 3/8" camera mounting plate in to 16mm socket. Compatible with 035 Super Clamp and 484RC2 or 486RC2 Ball Head for example. Diameter: 59,5mm



CAMERA MOUNTING ADAPTOR HEXAGONAL PIN 208HEX

Its main feature is the hexagonal pin, which, compared to the 208's round one, gives more grip when used to hold heavy cameras mounted on photo or video heads in combination with accessories like the super clamp 035.



SURVEY ADAPTOR 273

Converts tripod head screw from 3/8" threads to 5/8".




SURVEY PLATE ADAPTOR 324

This adaptor is made of two pieces: a 5/8" bushing with a 3/8" female attachment to connect it to a tripod and a removable plate 124mm diameter with a 5/8" male thread that should stay connected to the equipment. With the 324 it is possible to transform any Manfrotto tripod into a tripod compatible with the standard attachment interface system used in the survey and measuring industry.



SURVEY PLATE ADAPTOR ACCESSORY PLATE 358

Spare plate code for 324



SMALL ADAPTOR 088LBP

Converts 1/4" screw to 3/8".



PUMP CUP 241



1.2kg

Suction cup for small fixtures and lightweight equipment. Ø: 150mm.



PUMP CUP WITH FLAT BASE 241FB



0.62kg

Suction Cap for lightweight photographic and video equipment, such as 35 mm. SLR, digital cameras and lightweight video cameras. The 60 mm. diameter disc with a 3/8" W male thread is built in the pump cup and enables you to mount most of Manfrotto's heads.



CAMERA SUCTION MOUNT 241V



1.5kg



3kg

Attaches to most non-porous surfaces. Ideal camera support in automobile or next to a window.



DOUBLE BALL TILT HEAD 155RC



15cm



0.6kg



5kg



200PL-14

Not strictly a tripod head, but an extremely versatile camera support for compact and 35mm cameras used in conjunction with Super Clamp 035. Supplied with quick release camera plate and secondary safety lock.



PHOTO CLAMP

296

Can be fixed to surfaces up to 60mm thick. Has 2 x 3/8" male threads for mounting ball head and camera.



CAR WINDOW POD

243

Used for attaching either 482 or 234 head to a window or narrow sill. Attachment screw is 3/8". Ball head not provided.



SUPER CLAMP

035



0.25kg

This universal clamp can be securely mounted on any tube from 13 to 45mm. Attachment is 5/8" hexagonal socket.



BINOCULAR SUPER CLAMP

035BN



0.25kg

Designed to securely hold binoculars.



VARIABLE FRICTION ARM WITH QUICK RELEASE PLATE

244RC



1.11kg



4kg



200PL-14

Articulated arm with large locking knob. Variable friction and locking of arm obtained by adjusting the knob. Supplied with quick release camera plate with secondary safety lock based on the 200PL-14 camera plate mechanism. Ideal for mounting a photographic or video camera exactly at the angle you need it. Fits any 5/8" female socket, works especially well with 035 Super Clamp.



MAGIC ARM WITH QUICK RELEASE PLATE

143RC



1.09kg



4kg



200PL-14

Your extra arm in the studio. One lever locks three pivot points. Supplied with a quick release camera plate with secondary safety lock based on the 200PL-14 system. Ideal for mounting a camera or a camcorder exactly at the angle you need it. Fits any 5/8" female sockets, works especially well with 035 Super Clamp.



COLUMN CLAMP

349

Versatile clamp designed to work in conjunction with removable tripod columns of between 25 to 28mm diameter such as the 055 and 190 series tripods. The Column Clamp can be securely fixed to solid surfaces and bars up to 55 mm width. The column with head is inserted into the clamp and locked in position at the required height. The ideal accessory for nature photography or support for binoculars and scopes.

COLUMN CLAMP FOR CARBON CENTRE COLUMN

349C

Only for use with discontinued CARBON N ONE series tripod (440, 441, 443 and 444 models)

SPECIAL ADDITIONAL FEET

A complete line of foot conversions to adapt our tripods and monopods to all type of terrains in order to give them the maximum stability possible.



055SPK2
190SPK2
190SPK2N
440SPK2
441SPK2
439SPK2

RUBBER SPIKED FOOT STAINLESS STEEL

Reversible rubber/metal spiked feet (set of 3) supplied with a dedicated fixing tool. The spike is made of a special hard anodised aluminium alloy extremely resistant to corrosion.

055SPK2 for tripod: 055D, 055CL, 055PRO and 055NAT3.

190SPK2 for tripod: 190D, 190CL, 190PRO and 190NAT3 old model with 19mm leg.

190SPK2 for tripod: 190D, 190CL, 190PRO and 190NAT3.

440SPK2 for tripod: 724B, 728B, 190MF3 and 055MF4.

441SPK2 for tripod: 055MF3.

439SPK2 for tripod: 190MF4.



055SPK

RETRACTABLE SPIKED FOOT ADAPTER

Rubber feet (set of 3) for with retractable metal spike

For tripods: 055MF4.



055SCK2
190SCK2
190SCK2N
440SCK2
441SCK2
439SCK2

SUCTION CUP/RETRACTABLE SPIKE FEET

A rubber section cup feet (set of 3) with retractable stainless steel spike. The suction cup increases the footprint of the monopod by almost 20 times, giving much greater stability when needed. The foot can be removed and replaced at will.

055SCK2 for tripod: 055D, 055CL, 055PRO and 055NAT3.

190SCK2 for tripod: 190D, 190CL, 190PRO and 190NAT3 old model with 19mm leg.

190SCK2 for tripod: 190D, 190CL, 190PRO and 190NAT3.

440SCK2 for tripod: 724B, 728B, 190MF3 and 055MF4.

441SCK2 for tripod: 055MF3.

439SCK2 for tripod: 190MF4.



230

SNOW SHOES

Attach to tripod feet or monopods to provide stability in snow, mud or soft ground (set of 3).

For tripods: 190D, 190CL, 190PRO, 190NAT3, 190MF3, 190MF4, 055D, 055CL, 055PRO, 055NAT3, 055MF3, 055MF4, 458B, 028, 475, 058 and 161MK2.
Diameter: 138mm

PLATES

Plate Adaptors



SLIDING PLATE ADAPTOR **577**

Supplied with 1/4" and 3/8" camera fixing screws. Fixing 1/4" and 3/8" thread. 501PL sliding plate included.



HEXAGONAL PLATE ADAPTOR **625**

Supplied with 1/4" and 3/8" camera fixing screws. Fixing 1/4" and 3/8" thread. 030 hexagonal plate included. Equipped with 2 built-in spirit levels.



RECTANGULAR PLATE ADAPTOR **323**

Supplied with 1/4" camera fixing screws. Fixing 1/4" and 3/8" thread. 200PL rectangular plate included.



"DOVE TAIL" PLATE ADAPTOR **384**

Supplied with 1/4" and 3/8" camera fixing screws. Fixing 1/4" and 3/8" thread. 384PL and 384PLARCH plates included.



PLATE ADAPTOR **394**

Supplied with 1/4" and 3/8" camera fixing screws. Fixing 1/4" and 3/8" thread. 410PL plate included. Equipped with 2 built-in spirit levels.



SLIDING PLATE ADAPTOR **357**

Supplied with 1/4" and 3/8" camera fixing screws. Fixing 1/4" and 3/8" thread. 357PLV sliding plate included. Dimension: 140x44x6mm

Hexagonal Plates



HEXAGONAL PLATE 030
030-14 with 1/4" screw.
030-38 with 3/8" screw.



ARCH HEXAGONAL PLATE 030ARCH
Provides alignment for 90° shots with 35mm SLR camera.
030ARCH-14 with 1/4" screw.
030ARCH-38 with 3/8" screw.



HEXAGONAL PLATE 030HAS
For Hasselblad cameras.
Supplied with both 1/4" and 3/8" screw.



HEXAGONAL PLATE 130
130-14 with 1/4" screw.
130-38 with 3/8" screw.

Rectangular Plates



RECTANGULAR PLATE 200PL
200PL-14 with 1/4" screw.
200PL-38 with 3/8" screw.



ARCH RECTANGULAR PLATE 200PLARCH
Provides alignment for 90° shots with 35mm SLR camera
200PLARCH-14 with 1/4" screw.
200PLARCH-38 with 3/8" screw.



UNIVERSAL "ANTI TWIST" SPOTTING SCOPE PLATE 200USS
This adapter plate has been specifically designed to eliminate unwanted rotation of the spotting scope during viewing. Its universal design means it can be used to mount all makes of spotting scope, no matter what their foot shape (square, rectangular, trapezium), on any Manfrotto two-way head with rapid RC2 connector system. The adapter is made from machine-tooled aluminum with a black anodized finish. In addition to the standard 1/4" screw, it has two grub set screws to lock the spotting scope securely in position.

Special Plates



LARGE PLATE 030L
Large 10cm x 10cm plate with 1/4" and 3/8" screw.



"DOVE TAIL" PLATE 384PL
384PL-14 with 1/4" screw.
384PL-38 with 3/8" screw.



"DOVE TAIL" ARCH. PLATE 384PLARCH
Provides alignment for 90° shots with 35mm SLR camera
384PLARCH-14 with 1/4" screw.
384PLARCH-38 with 3/8" screw.



ACCESSORY PLATE 410PL
410PL-14 with 1/4" screw.
410PL-38 with 3/8" screw.



ACCESSORY PLATE 400PL
400PL-LOW = 13mm H.
400PL-MED = 23mm H.
400PL-HIG = 42mm H.



PLATE 501PL
Supplied with 1/4" and 3/8" camera fixing screws.
Dimension: 86x38x11mm



SLIDING PLATE 357PLV
Supplied with 2 x 1/4" and 2 x 3/8" camera fixing screws.
Dimension: 140x44x6mm